



The eP-LL195 Flexible cable with black PE jacket offers users high quality, low cost flexible jumper cable. evissaP offers its eP-LL195 Flexible cable assemblies in a wide variety of connector configurations, eP-LL195 Flexible cable assemblies are built using lead free solder in combination with state of-the-art induction soldering techniques.

Features

- eP-LL195 Flexible
- SMA male and SMA female connectors
- 100% VSWR test to 3 GHz
- 100% Hi-pot and continuity tests
- Standard delivery <21 days from order
- RoHS compliant per evissaP RoHS statement

Overview

Impedance	50 ohms
Frequency Range	DC-3 GHz
Cable	eP-LL195
Cable O.D.	.195" nominal

Configuration

Connector 1	SMA male Gold plated brass body
Connector 2	SMA female Gold plated brass body

Application

- WLL, GPS, WLAN
- Mobil Antennas
- Wireless Communication Sysytem

evissaP Standards

When ordering, please specify cable assembly length in inches. Example: eP2078R-12.5 specifies a 12.5" long cable assembly. Label will have evissaP P/N and Date Code. Shipment will include evissaP's standard C of C. evissaP web posted warranty and Ters and Condi-tions applies. FOB is evissaP's San Jose, CA US facility

Connector options available for eP-LL195 cable

- * BNC ST and RT/A male, female and bulkhead
- * Type N ST and RT male, female and bulkhead
- * TNC ST male, female and bulkhead


Electrical Specifications @ +25°C		Unit
Frequency range	DC-3	GHz
Maximum VSWR	1.35	:1
Cable Typical velocity of propagation	69.5	%

Typical Performance @+25°C	DC-1GHz	1-2GHz	2-3GHz
VSWR (S11) (:1) typ. max.@12 in.	1.18	1.09	1.05
Insertion Loss (S21) (dB) typ. max. @12 in.	0.15	0.20	0.27
For any length (L in.), estimated insertion loss: C + (S21 value above-C) * (L/12) , Connector loss is C = 2 * .03 √f(GHz)			


Bulk cable specifications	
Temperature range	-40to +80° C
Cable Type	eP-LL195
Cable outer diameter	.195" nominal
Inner conductor/finish	Bare Copper
Dielectric type	Foam PE
Jacket material	PE

Connector specifications	Connector 1	Connector 2
Configuration	Straight	Straight
Connector Type	SMA male	SMA female
Body hex size	N/A	0.256"
Coupling nut hex size	0.313"	N/A
Coupling nut material/finish	Au	N/A
Connector body material/finish	Au	Au
Dielectric type	PTFE	PTFE

Typical performance data for 12" cable @+25°



Outline drawing



Standard length tolerance	
L (inches)	Tolerance (inches)
2.0 - 5.9	+/-0.125
6.0 - 11.9	+/-0.187
12.0 - 23.9	+/-0.250
24.0 - 35.9	+/-0.313
36.0 - 47.9	+/-0.375
48.0 - 59.9	+/-0.500
60.0 - 71.9	+/-0.563
72.0 - 83.9	+/-0.625
>83.9	Please contact evissaP

evissaP offers its eP-LL195 Flexible cable assemblies in a wide variety of connector configurations, eP-LL195 Flexible cable assemblies are built using lead free solder in combination with state-of-the art induction soldering techniques. If you cannot find the exact eP-formable cable assembly you require, please submit a request along with your requirement information.

The information in this publication is believed to be accurate and reliable. However, no responsibility is assumed by evissaP, Inc. ("eP") for its use, nor for any infringement of patents, or other rights of third parties, resulting from its use. No license is granted by implication or otherwise under any patent or patent rights of evissaP. evissaP reserves the right to change specifications, prices and any other information at any time without prior notice.